

TECHNICAL FEATURES

- ✓ Indicator: buzzer and led display;
- ✓ Handle to adjust sensitivity;
- ✓ Power supply: One 9 volt battery;
- ✓ Reel with lock and tip holder;
- ✓ Tip diameter: 12 mm;
- ✓ Reel with drum in plastic and steel frame;
- ✓ Drum diameter: 260 mm (30-50 m), diam. 320 mm (100-150-200 m).



This level meter is used to measure the level of groundwater inside open tube piezometers, Casagrande piezometers, irrigation wells, and to measure the water level in waterways, lakes and reservoirs. It is composed of a plastic reel mounted on a steel frame. The graduated signal cable is wrapped on the reel and it can be either round or flat. The stainless steel tip is attached to the

end of the cable.

When the tip comes into contact with the water, it closes the electric circuit activating the light and buzzer. The water level is shown on the graduated cable.

Easy to carry around with the ergonomic handle.

We reserve the right to carry out modifications to our products and their specifications

CE product compliant with European directives

CABLE SPECIFICATIONS

Flat cable	<i>graduated</i>	millimetre
	<i>conductors</i>	2
	<i>external jacket</i>	transparent polyethylene
	<i>dimensions</i>	10x1 mm
	<i>available in length</i>	30-50-100-150-200-250-300 m
Round cable	<i>graduated</i>	centimetre
	<i>conductors</i>	2 + kevlar core
	<i>external jacket</i>	transparent polyethylene
	<i>dimensions</i>	4.7 mm outer diameter
	<i>available in length</i>	30-50-100-150-200-250-300 m